

The luacolor package

Heiko Oberdiek*

2020-02-24 v1.15

Abstract

Package luacolor implements color support based on LuaTeX's node attributes.

Contents

1	Documentation	2
1.1	Introduction	2
1.2	Usage	2
1.3	Limitations	2
2	Implementation	3
2.1	Catcodes and identification	3
2.2	Check for LuaTeX	4
2.3	Check for disabled colors	4
2.4	Load module and check version	4
2.5	Find driver	4
2.6	Attribute setting	5
2.7	Whatsit insertion	5
2.8	<code>\pdfxform/\saveboxresource</code> support	6
2.9	Lua module	7
2.9.1	Driver detection	8
2.9.2	Color strings	8
2.9.3	Attribute register	9
2.9.4	Whatsit insertion	9
3	Installation	11
3.1	Download	11
3.2	Bundle installation	12
3.3	Package installation	12
3.4	Refresh file name databases	12
3.5	Some details for the interested	12
4	History	13
	[2007/12/12 v1.0]	13
	[2009/04/10 v1.1]	13
	[2010/03/09 v1.2]	13
	[2010/12/13 v1.3]	13
	[2011/03/29 v1.4]	13
	[2011/04/22 v1.5]	13

*Please report any issues at <https://github.com/ho-tex/luacolor/issues>

[2011/04/23 v1.6]	14
[2011/10/22 v1.7]	14
[2011/11/01 v1.8]	14
[2016/05/13 v1.9]	14
[2016/05/16 v1.10]	14
[2018/11/22 v1.11]	14
[2019/07/25 v1.12]	14
[2019/11/29 v1.13]	14
[2020-02-22 v1.14]	14
[2020-02-24 v1.15]	14

5 Index **15**

1 Documentation

1.1 Introduction

This package uses a LuaTeX's attribute register to to annotate nodes with color information. If a color is set, then the attribute register is set to this color and all nodes created in its scope (current group) are annotated with this attribute. Now the color property behaves much the same way as the font property.

1.2 Usage

Package `color` is loaded automatically by this package `luacolor`. If you need a special driver option or you prefer package `xcolor`, then load it before package `luacolor`, for example:

```
\usepackage[dvipdfmx]{xcolor}
```

The package `luacolor` is loaded without options:

```
\usepackage{luacolor}
```

It is able to detect PDF mode and DVI drivers are differentiated by its color specials. Therefore the package do need driver options.

Then it redefines the color setting commands to set attributes instead of what-sits for color.

At last the attribute annotations of the nodes in the output box must be analyzed to insert the necessary color whatsits. Currently LuaTeX lacks an appropriate callback function. Therefore package `atbegshi` is used to get control before a box is shipped out.

`\luacolorProcessBox {⟨box⟩}`

Macro `\luacolorProcessBox` processes the box $\langle box \rangle$ in the previously described manner. It is automatically called for pages, but not for XForm objects. Before passing a box to `\pdfxform`, call `\luacolorProcessBox` first.

1.3 Limitations

Ligatures with different colored components: Package `luacolor` sees the ligature after the paragraph building and page breaking, when a page is to be shipped out. Therefore it cannot break ligatures, because the components might occupy different space. Therefore it is the responsibility of the

ligature forming process to deal with different colored glyphs that form a ligature. The user can avoid the problem entirely by explicitly breaking the ligature at the places where the color changes.

...

2 Implementation

1 (*package)

2.1 Catcodes and identification

```

2 \begingroup\catcode61\catcode48\catcode32=10\relax%
3  \catcode13=5 % ^^M
4  \endlinechar=13 %
5  \catcode123=1 % {
6  \catcode125=2 % }
7  \catcode64=11 % @
8  \def\x{\endgroup
9    \expandafter\edef\csname LuaCol@AtEnd\endcsname{%
10     \endlinechar=\the\endlinechar\relax
11     \catcode13=\the\catcode13\relax
12     \catcode32=\the\catcode32\relax
13     \catcode35=\the\catcode35\relax
14     \catcode61=\the\catcode61\relax
15     \catcode64=\the\catcode64\relax
16     \catcode123=\the\catcode123\relax
17     \catcode125=\the\catcode125\relax
18   }%
19 }%
20 \x\catcode61\catcode48\catcode32=10\relax%
21 \catcode13=5 % ^^M
22 \endlinechar=13 %
23 \catcode35=6 % #
24 \catcode64=11 % @
25 \catcode123=1 % {
26 \catcode125=2 % }
27 \def\TMP@EnsureCode#1#2{%
28   \edef\LuaCol@AtEnd{%
29     \LuaCol@AtEnd
30     \catcode#1=\the\catcode#1\relax
31   }%
32   \catcode#1=#2\relax
33 }
34 \TMP@EnsureCode{34}{12}% "
35 \TMP@EnsureCode{39}{12}% '
36 \TMP@EnsureCode{40}{12}% (
37 \TMP@EnsureCode{41}{12}% )
38 \TMP@EnsureCode{42}{12}% *
39 \TMP@EnsureCode{43}{12}% +
40 \TMP@EnsureCode{44}{12}% ,
41 \TMP@EnsureCode{45}{12}% -
42 \TMP@EnsureCode{46}{12}% .
43 \TMP@EnsureCode{47}{12}% /
44 \TMP@EnsureCode{58}{12}% :
45 \TMP@EnsureCode{60}{12}% <
46 \TMP@EnsureCode{62}{12}% >
47 \TMP@EnsureCode{91}{12}% [

```

```

48 \TMP@EnsureCode{93}{12}% ]
49 \TMP@EnsureCode{95}{12}% _ (other!)
50 \TMP@EnsureCode{96}{12}% ‘
51 \edef\LuaCol@AtEnd{\LuaCol@AtEnd\noexpand\endinput}

Package identification.
52 \NeedsTeXFormat{LaTeX2e}
53 \ProvidesPackage{luacolor}%
54 [2020-02-24 v1.15 Color support via LuaTeX’s attributes (HO)]

```

2.2 Check for LuaTeX

Without LuaTeX there is no point in using this package.

```

55 \RequirePackage{color}

56 \ifx\directlua\@undefined
57 \PackageError{luacolor}{%
58 This package may only be run using LuaTeX%
59 }\@ehc
60 \expandafter\LuaCol@AtEnd
61 \fi%

```

2.3 Check for disabled colors

```

62 \ifcolors@
63 \else
64 \PackageWarningNoLine{luacolor}{%
65 Colors are disabled by option ‘monochrome’%
66 }%
67 \def\set@color{}%
68 \def\reset@color{}%
69 \def\set@page@color{}%
70 \def\define@color#1#2{}%
71 \expandafter\LuaCol@AtEnd
72 \fi%

```

2.4 Load module and check version

```

73 \directlua{%
74 require("luacolor")%
75 }

76 \begingroup
77 \edef\x{\directlua{tex.write("2020-02-24 v1.15")}}%
78 \edef\y{%
79 \directlua{%
80 if oberdiek.luacolor.getversion then %
81 oberdiek.luacolor.getversion()%
82 end%
83 }%
84 }%
85 \ifx\x\y
86 \else
87 \PackageError{luacolor}{%
88 Wrong version of lua module.\MessageBreak
89 Package version: \x\MessageBreak
90 Lua module: \y
91 }\@ehc
92 \fi
93 \endgroup

```

2.5 Find driver

```
94 \ifnum\outputmode=\@ne
95 \else
96   \begingroup
97     \def\current@color{}%
98     \def\reset@color{}%
99     \setbox\z@=\hbox{%
100       \begingroup
101         \set@color
102       \endgroup
103     }%
104     \edef\reserved@a{%
105       \directlua{%
106         oberdiek.luacolor.dvidetect()}%
107     }%
108   }%
109   \ifx\reserved@a\@empty
110     \PackageError{luacolor}{%
111       DVI driver detection failed because of\MessageBreak
112       unrecognized color \string\special
113     }\@ehc
114   \endgroup
115   \expandafter\expandafter\expandafter\LuaCol@AtEnd
116 \else
117   \PackageInfo{luacolor}{%
118     Type of color \string\special: \reserved@a
119   }\@gobble}%
120 \fi%
121 \endgroup
122 \fi
```

2.6 Attribute setting

\LuaCol@Attribute

```
123 \newattribute\LuaCol@Attribute
124 \let\LuaCol@setattribute\setattribute
125 \directlua{%
126   oberdiek.luacolor.setattribute(\number\allocationnumber)%
127 }
```

\set@color

```
128 \protected\def\set@color{%
129   \LuaCol@setattribute\LuaCol@Attribute{%
130     \directlua{%
131       oberdiek.luacolor.get("\luaescapestring{\current@color}")%
132     }%
133   }%
134 }
```

\reset@color

```
135 \def\reset@color{}
```

2.7 Whatsit insertion

\luacolorProcessBox

```
136 \def\luacolorProcessBox#1{%
137   \directlua{%
```

```

138 oberdiek.luacolor.process(\number#1)%
139 }%
140 }

```

```

141 \RequirePackage{atbegshi}[2011/01/30]
142 \AtBeginShipout{%
143 \luacolorProcessBox\AtBeginShipoutBox
144 }

```

```

Set default color.
145 \set@color

```

2.8 \pdfxform/\saveboxresource support

```

146 \ifnum\outputmode=\@ne
147 \let\LuaCol@org@pdfxform\saveboxresource

```

First we need some helpers to allow expandable code to parse keyword style arguments:

```

148 \def\LuaCol@iii@ii#1#2#3{#3{#1}{#2}}
149 \def\LuaCol@ii@i#1#2{#2#1}
150 \def\LuaCol@if@keyword#1#2#3{%
151 \expanded{\unexpanded{\LuaCol@iii@ii{#2}{#3}}\expandafter}%
152 \directlua{%
153 token.put_next(token.create(token.scan_keyword(token.scan_string()))
154 and '@firstoftwo'
155 or '@secondoftwo'))
156 }{#1}%
157 }

```

The following macro scans a integer and expands to a token equivalent to a chardef whose value corresponds to the scanned integer. This allows the integer to be passed around as a undelimited argument.

```

158 \def\LuaCol@scan@number{%
159 \directlua{
160 token.put_next(token.new(token.scan_int(), token.command_id'char_given'))
161 }%
162 }

```

TeX primitives like `\saveboxresource` read braced arguments in a special way. Especially they expand everything until they find a left brace. To simulate this, we use Lua to expand everything else:

```

163 \def\LuaCol@scan@tobraces{%
164 \directlua{
165 local relax, space = token.command_id'relax', token.command_id'spacer'
166 local t
167 repeat
168 t = token.scan_token()
169 until not (t.command == relax or t.command == space)
170 token.put_next(t)
171 }%
172 }
173 \def\LuaCol@scan@boxresource@i#1#2{%
174 \LuaCol@if@keyword{attr}{%
175 \expanded{\unexpanded{\LuaCol@scan@boxresource@iI{#1#2attr}}}%
176 \expandafter\expandafter\expandafter}%
177 \LuaCol@scan@tobraces
178 }{%
179 \LuaCol@scan@boxresource@ii{#1#2}%
180 }%

```

```

181 }
182 \def\LuaCol@scan@boxresource@ii#1#2{\LuaCol@scan@boxresource@ii{#1{#2}}}
183 \def\LuaCol@scan@boxresource@ii#1{%
184   \LuaCol@if@keyword{resources}{%
185     \expanded{\unexpanded{\LuaCol@scan@boxresource@iii{#1resources}}}%
186     \expandafter\expandafter\expandafter}%
187   \LuaCol@scan@tobracer
188 }{%
189   \LuaCol@scan@boxresource@iii{#1}%
190 }%
191 }
192 \def\LuaCol@scan@boxresource@iii#1#2{\LuaCol@scan@boxresource@iii{#1{#2}}}
193 \def\LuaCol@scan@boxresource@iii#1{%
194   \LuaCol@if@keyword{margin}{%
195     \expanded{\unexpanded{\LuaCol@scan@boxresource@iv{#1margin }}}%
196     \expandafter\expandafter\expandafter}%
197   \LuaCol@scan@number
198 }{%
199   \LuaCol@scan@boxresource@iv{#1}{}%
200 }%
201 }
202 \def\LuaCol@scan@boxresource@iv#1#2{%
203   \expanded{\unexpanded{\LuaCol@scan@boxresource@v{#1#2}}}%
204   \expandafter\expandafter\expandafter}%
205   \LuaCol@scan@number
206 }
207 \def\LuaCol@scan@boxresource@v#1#2{%
208   \luacolorProcessBox{#2}%
209   \LuaCol@org@pdfxform#1#2%
210 }
211 }

```

This could be written in Lua, but at least upto LuaTeX 1.11, feeding back too many tokens from Lua to TeX triggers a segmentation fault. This is written in Lua so the integer setting is expandable and does not interfere with a preceding `\immediate`.

```

212 \protected\def\saveboxresource{%
213   \LuaCol@if@keyword{type}{%
214     \expandafter
215     \expanded{\unexpanded{\LuaCol@scan@boxresource@i{type }}}%
216     \expandafter\expandafter\expandafter}%
217   \LuaCol@scan@number
218 }{%
219   \LuaCol@scan@boxresource@i{}{}%
220 }%
221 }

```

Legacy alias.

```

222 \let\pdfxform\saveboxresource
223 \fi
224 \LuaCol@AtEnd%
225 </package>

```

2.9 Lua module

```
226 <*lua>
```

Box zero contains a `\hbox` with the color `\special`. That is analyzed to get the prefix for the color setting `\special`.

```
227 oberdiek = oberdiek or {}
```

```

228 local luacolor = oberdiek.luacolor or {}
229 oberdiek.luacolor = luacolor

getversion()
230 function luacolor.getversion()
231   tex.write("2020-02-24 v1.15")
232 end

2.9.1 Driver detection

233 local ifpdf = tonumber(tex.outputmode or tex.pdfoutput) > 0
234 local prefix
235 local prefixes = {
236   dvips = "color ",
237   dvipdfm = "pdf:sc ",
238   truetex = "textcolor:",
239   pctexps = "ps::",
240 }
241 local patterns = {
242   [ "^color " ] = "dvips",
243   [ "^pdf: *begincolor " ] = "dvipdfm",
244   [ "^pdf: *bcolor " ] = "dvipdfm",
245   [ "^pdf: *bc " ] = "dvipdfm",
246   [ "^pdf: *setcolor " ] = "dvipdfm",
247   [ "^pdf: *scolor " ] = "dvipdfm",
248   [ "^pdf: *sc " ] = "dvipdfm",
249   [ "^textcolor:" ] = "truetex",
250   [ "^ps::" ] = "pctexps",
251 }

info()
252 local function info(msg, term)
253   local target = "log"
254   if term then
255     target = "term and log"
256   end
257   texio.write_nl(target, "Package luacolor info: " .. msg .. ".")
258   texio.write_nl(target, "")
259 end

dvidetect()
260 function luacolor.dvidetect()
261   local v = tex.box[0]
262   assert(v.id == node.id("hlist"))
263   for v in node.traverse_id(node.id("whatsit"), v.head) do
264     if v and v.subtype == node.subtype("special") then
265       local data = v.data
266       for pattern, driver in pairs(patterns) do
267         if string.find(data, pattern) then
268           prefix = prefixes[driver]
269           tex.write(driver)
270           return
271         end
272       end
273       info("\\special{" .. data .. "}", true)
274       return
275     end
276   end
277   info("Missing \\special", true)

```

```
278 end
```

2.9.2 Color strings

```
279 local map = {  
280   n = 0,  
281 }
```

get()

```
282 function luacolor.get(color)  
283   tex.write("" .. luacolor.getvalue(color))  
284 end
```

getvalue()

```
285 function luacolor.getvalue(color)  
286   local n = map[color]  
287   if not n then  
288     n = map.n + 1  
289     map.n = n  
290     map[n] = color  
291     map[color] = n  
292   end  
293   return n  
294 end
```

2.9.3 Attribute register

setattribute()

```
295 local attribute  
296 function luacolor.setattribute(attr)  
297   attribute = attr  
298 end
```

getattribute()

```
299 function luacolor.getattribute()  
300   return attribute  
301 end
```

2.9.4 Whatsit insertion

```
302 local LIST = 1  
303 local LIST_LEADERS = 2  
304 local LIST_DISC = 3  
305 local COLOR = 4  
306 local RULE = node.id("rule")  
307 local node_types = {  
308   [node.id("hlist")] = LIST,  
309   [node.id("vlist")] = LIST,  
310   [node.id("rule")] = COLOR,  
311   [node.id("glyph")] = COLOR,  
312   [node.id("disc")] = LIST_DISC,  
313   [node.id("whatsit")] = {  
314     [node.subtype("special")] = COLOR,  
315     [node.subtype("pdf_literal")] = COLOR,  
316     [node.subtype("pdf_save")] = COLOR,  
317     [node.subtype("pdf_restore")] = COLOR, -- probably not needed  
318 -- TODO (DPC) [node.subtype("pdf_refximage")] = COLOR,  
319   },
```

```

320 [node.id("glue")] =
321   function(n)
322     if n.subtype >= 100 then -- leaders
323       if n.leader.id == RULE then
324         return COLOR
325       else
326         return LIST_LEADERS
327       end
328     end
329   end,
330 }

get_type()

331 local function get_type(n)
332   local ret = node_types[n.id]
333   if type(ret) == 'table' then
334     ret = ret[n.subtype]
335   end
336   if type(ret) == 'function' then
337     ret = ret(n)
338   end
339   return ret
340 end

341 local mode = 2 -- luatex.pdfliteral.direct
342 local WHATSIT = node.id("whatsit")
343 local SPECIAL = node.subtype("special")
344 local PDFLITERAL = node.subtype("pdf_literal")
345 local DRY_FALSE = false
346 local DRY_TRUE = true

traverse()

347 local function traverse(list, color, dry)
348   if not list then
349     return color
350   end
351   local head
352   if get_type(list) == LIST then
353     head = list.head
354   elseif get_type(list) == LIST_DISC then
355     head = list.replace
356   else
357     texio.write_nl("!!! Error: Wrong list type: " .. node.type(list.id))
358     return color
359   end
360 (debug)texio.write_nl("traverse: " .. node.type(list.id))
361   for n in node.traverse(head) do
362 (debug)texio.write_nl(" node: " .. node.type(n.id))
363     local t = get_type(n)
364 (debug)texio.write_nl("TYPE " .. tostring(t) .. " " .. tostring(node.type(node.getid(n))) .. " " .. tos
365     if t == LIST or t == LIST_DISC then
366       color = traverse(n, color, dry)
367     elseif t == LIST_LEADERS then
368       local color_after = traverse(n.leader, color, DRY_TRUE)
369       if color == color_after then
370         traverse(n.leader, color, DRY_FALSE or dry)
371       else
372         traverse(n.leader, '', DRY_FALSE or dry)

```

The color status is unknown here, because the leader box will or will not be set.

```
373     color = ''
374     end
375 elseif t == COLOR then
376     local v = node.has_attribute(n, attribute)
377     if v then
378         local newColor = map[v]
379         if newColor ~= color then
380             color = newColor
381             if dry == DRY_FALSE then
382                 local newNode
383                 if ifpdf then
384                     newNode = node.new(WHATSIT, PDFLITERAL)
385                     newNode.mode = mode
386                     newNode.data = color
387                 else
388                     newNode = node.new(WHATSIT, SPECIAL)
389                     newNode.data = prefix .. color
390                 end
391                 head = node.insert_before(head, n, newNode)
392             end
393         end
394     end
395 end
396 end
397 if get_type(list) == LIST then
398     list.head = head
399 else
400     list.replace = head
401 end
402 return color
403 end
```

process()

```
404 function luacolor.process(box)
405     local color = ""
406     local list = tex.getbox(box)
407     traverse(list, color, DRY_FALSE)
408 end
```

For recent versions of luaotfload, we can register a callback to control how coloring glyph is handled for the color feature.

```
409 if luaotfload.set_colorhandler then
410     local set_attribute = node.direct.set_attribute
411     luaotfload.set_colorhandler(function(head, n, color)
412         set_attribute(n, attribute, luacolor.getvalue(color))
413         return head, n
414     end)
415 end
416  $\langle$ /lua
```

3 Installation

3.1 Download

Package. This package is available on CTAN¹:

¹[CTAN:pkg/luacolor](https://ctan.org/pkg/luacolor)

[CTAN:macros/latex/contrib/luacolor/luacolor.dtx](#) The source file.

[CTAN:macros/latex/contrib/luacolor/luacolor.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘luacolor’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/luacolor.tds.zip](#)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:pkg/tds](#)). Directories with `texmf` in their name are usually organized this way.

3.2 Bundle installation

Unpacking. Unpack the `luacolor.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip luacolor.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDS:scripts/luacolor/` for scripts that need further installation steps.

3.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain T_EX:

```
tex luacolor.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
luacolor.sty → tex/latex/luacolor/luacolor.sty
luacolor.lua → scripts/luacolor/luacolor.lua
luacolor.pdf → doc/latex/luacolor/luacolor.pdf
luacolor.dtx → source/latex/luacolor/luacolor.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

3.4 Refresh file name databases

If your T_EX distribution (T_EX Live, MiK_TE_X, ...) relies on file name databases, you must refresh these. For example, T_EX Live users run `texhash` or `mktexlsr`.

3.5 Some details for the interested

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain T_EX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the `autodetect` routine about your intention:

```
latex \let\install=y\input{luacolor.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex luacolor.dtx
makeindex -s gind.ist luacolor.idx
pdflatex luacolor.dtx
makeindex -s gind.ist luacolor.idx
pdflatex luacolor.dtx
```

4 History

[2007/12/12 v1.0]

- First public version.

[2009/04/10 v1.1]

- Fixes for changed syntax of `\directlua` in Lua_TE_X 0.36.

[2010/03/09 v1.2]

- Adaptation for package `luatex 2010/03/09 v0.4`.

[2010/12/13 v1.3]

- Support for `\pdfxform` added.
- Loaded package `luatexbase-attr` recognized.
- Update for Lua_TE_X: ‘list’ fields renamed to ‘head’ in v0.65.0.

[2011/03/29 v1.4]

- Avoid `whatsit` insertion if option `monochrome` is used (thanks Manuel Pégourié-Gonnard).

[2011/04/22 v1.5]

- Bug fix by Manuel Pégourié-Gonnard: A typo prevented the detection of `whatsits` and applying color changes for `\pdfliteral` and `\special` nodes that might contain typesetting material.
- Bug fix by Manuel Pégourié-Gonnard: Now colors are also applied to leader boxes.
- Unnecessary color settings are removed for leaders boxes, if after the leader box the color has not changed. The costs are a little runtime, leader boxes are processed twice.
- Additional `whatsits` that are colored: `pdf_refximage`.
- Workaround for bug with `node.insert_before` removed for the version after Lua_TE_X 0.65, because bug was fixed in 0.27. (Thanks Manuel Pégourié-Gonnard.)

[2011/04/23 v1.6]

- Bug fix for nested leader boxes.
- Bug fix for leader boxes that change color, but are not set because of missing place.
- Version check for Lua module added.

[2011/10/22 v1.7]

- Lua functions `getattribute` and `getvalue` added to tell other external Lua functions the attribute register number for coloring.

[2011/11/01 v1.8]

- Use of `node.subtype` instead of magic numbers.

[2016/05/13 v1.9]

- More use of `node.subtype` instead of magic numbers.
- luatex 85 updates

[2016/05/16 v1.10]

- Documentation updates.

[2018/11/22 v1.11]

- handle issue 43.
- removed pre-0.65 stuff

[2019/07/25 v1.12]

- removed uses of module function, see PR70

[2019/11/29 v1.13]

- Documentation updates.
- Use `iftex` directly.

[2020-02-22 v1.14]

- Drop use of `iftex ltxcmds` and `infwarerr`.
- Assume `l luatex` preloaded into format (true since 2015).
- Patch `\saveboxresource` rather than `\pdfxform` (keep old name as alias).
- Grab the number via Lua so that a `\immediate` prefix still works with `\saveboxresource/\pdfxform`.
- Added handler for the color feature of `luaotfload`

[2020-02-24 v1.15]

- Grab all possible arguments for `\saveboxresource/\pdfxform`

5 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	
<code>\@ehc</code>	59, 91, 113
<code>\@empty</code>	109
<code>\@gobble</code>	119
<code>\@ne</code>	94, 146
<code>\@undefined</code>	56
<code>\@</code>	273, 277
A	
<code>\allocationnumber</code>	126
<code>\AtBeginShipout</code>	142
<code>\AtBeginShipoutBox</code>	143
C	
<code>\catcode</code>	2, 3, 5, 6, 7, 11, 12, 13, 14, 15, 16, 17, 20, 21, 23, 24, 25, 26, 30, 32
<code>\csname</code>	9
<code>\current@color</code>	97, 131
D	
<code>\define@color</code>	70
<code>\directlua</code>	56, 73, 77, 79, 105, 125, 130, 137, 152, 159, 164
<code>\dvidetect()</code>	260
E	
<code>\endcsname</code>	9
<code>\endinput</code>	51
<code>\endlinechar</code>	4, 10, 22
<code>\expanded</code> ..	151, 175, 185, 195, 203, 215
G	
<code>\get()</code>	282
<code>\get_type()</code>	331
<code>\getattribute()</code>	299
<code>\getvalue()</code>	285
<code>\getversion()</code>	230
H	
<code>\hbox</code>	99
I	
<code>\ifcolors@</code>	62
<code>\ifnum</code>	94, 146
<code>\ifx</code>	56, 85, 109
<code>\info()</code>	252
L	
<code>\LuaCol@AtEnd</code> ..	28, 29, 51, 60, 71, 115, 224
<code>\LuaCol@Attribute</code>	123, 129
<code>\LuaCol@if@keyword</code>	150, 174, 184, 194, 213
<code>\LuaCol@ii@i</code>	149
<code>\LuaCol@iii@i@ii</code>	148, 151
<code>\LuaCol@org@pdfxform</code>	147, 209
<code>\LuaCol@scan@boxresource@i</code>	173, 215, 219
<code>\LuaCol@scan@boxresource@iI</code>	175, 182
<code>\LuaCol@scan@boxresource@ii</code>	179, 182, 183
<code>\LuaCol@scan@boxresource@iiI</code>	185, 192
<code>\LuaCol@scan@boxresource@iii</code>	189, 192, 193
<code>\LuaCol@scan@boxresource@iv</code>	195, 199, 202
<code>\LuaCol@scan@boxresource@v</code> ..	203, 207
<code>\LuaCol@scan@number</code> ..	158, 197, 205, 217
<code>\LuaCol@scan@tobrace</code> ..	163, 177, 187
<code>\LuaCol@setattribute</code>	124, 129
<code>\luacolorProcessBox</code> ..	2, 136, 143, 208
<code>\luaescapestring</code>	131
M	
<code>\MessageBreak</code>	88, 89, 111
N	
<code>\NeedsTeXFormat</code>	52
<code>\newattribute</code>	123
<code>\number</code>	126, 138
O	
<code>\outputmode</code>	94, 146
P	
<code>\PackageError</code>	57, 87, 110
<code>\PackageInfo</code>	117
<code>\PackageWarningNoLine</code>	64
<code>\pdfxform</code>	222
<code>\process()</code>	404
<code>\protected</code>	128, 212
<code>\ProvidesPackage</code>	53
R	
<code>\RequirePackage</code>	55, 141
<code>\reserved@a</code>	104, 109, 118
<code>\reset@color</code>	68, 98, 135
S	
<code>\saveboxresource</code>	147, 212, 222
<code>\set@color</code>	67, 101, 128, 145
<code>\set@page@color</code>	69
<code>\setattribute</code>	124
<code>\setattribute()</code>	295
<code>\setbox</code>	99
<code>\special</code>	112, 118

	T		X
<code>\the</code> . . .	10, 11, 12, 13, 14, 15, 16, 17, 30	<code>\x</code>	8, 20, 77, 85, 89
<code>\TMP@EnsureCode</code>	27,		
	34, 35, 36, 37, 38, 39, 40, 41,	Y	
	42, 43, 44, 45, 46, 47, 48, 49, 50	<code>\y</code>	78, 85, 90
<code>\traverse()</code>	<u>347</u>		
	U		Z
<code>\unexpanded</code>	151, 175, 185, 195, 203, 215	<code>\z@</code>	99