

Numbering individual lines of equation array's

Johannes Braams
TeXniek
Kersengaarde 33
2723 BP Zoetermeer
The Netherlands
Internet: TeXniek at braams.cistron.nl
2004/04/15

This package defines the `subeqnarray` and `subeqnarray*` environments, which behave like the equivalent `eqnarray` and `eqnarray*` environments, except that the individual lines are numbered like 1a, 1b, 1c, etc.

To refer to these numbers an extra label command `\slabel` has been defined.
Many of this code was taken from `latex.tex` and modified for this purpose.

1 Initial Code

`\c@subequation` We need to allocate a new counter for the `subequation` environment. It is reset by the `equation` counter.

```
1 (*package)
2 \newcounter{subequation}[equation]
```

`\thesubequation` The representation o the counter `subequation` includes the `equation` counter
3 `\def\thesubequation{\theequation\alph{subequation}}`

2 Option Handling

The standard L^AT_EX options `leqno` and `fleqn` are recognised by this package.

```
4 %
5 % When \Opt{leqno} is used the equation numbers should appear on
6 % the left side of the equation. The numbers are generated by
7 % |\c@subeqnnum| which needs a different definition to acheive this
8 % effect.
9 % \begin{macrocode}
10 \DeclareOption{leqno}{%
11   \def\c@subeqnnum{\hbox to .01\p@{}{\rlap{\reset@font\rmfamily
12     \hspace{-\displaywidth(\thesubequation)}}}}
13 \DeclareOption{reqno}{%
14   \def\c@subeqnnum{\reset@font\rmfamily (\thesubequation)}}}
```

The default definition of `\c@subeqnnum`.

```
13 \DeclareOption{reqno}{%
14   \def\c@subeqnnum{\reset@font\rmfamily (\thesubequation)}}}
```

When the option `fleqn` is used, the equations have to be printed flush left, with an indent of `\mathindent`; the equations are separated from the surrounding text by `\topsep` (plus `\partopsep` if necessary) and the width of the display is `\linewidth`.

```

15 \DeclareOption{fleqn}{%
16   \def\subeqn@start{%
17     \tabskip\mathindent
18     \abovedisplayskip\topsep
19     \ifvmode\advance\abovedisplayskip\partopsep\fi
20     \belowdisplayskip\abovedisplayskip
21     \belowdisplayshortskip\abovedisplayskip
22     \abovedisplayshortskip\abovedisplayskip
23     $$\everycr{}\halign to \linewidth{}% $$

```

The default will be to have displayed equations to the width of `\displaywidth`.

```

24 \DeclareOption{deqn}{%
25   \def\subeqn@start{%
26     \tabskip@centering
27     $$\everycr{}\halign to \displaywidth{}% $$

```

We don't support any other options

```
28 \DeclareOption*{\OptionNotUsed}
```

3 Executing Options

Make sure the `\@eqnnum` is defined by specifying `reqno` as a default option. Specifying `deqn` as a default option defines `\subeqn@start`.

```
29 \ExecuteOptions{reqno,deqn}
```

Now see if the user specified any options.

```
30 \ProcessOptions
```

4 The main code

`\slabel` A new label command to refer to subequations. It works like the `\label` command and was taken from `latex.tex`.

```

\slabel{FOO} writes the following on file \auxout
\newlabel{FOO}{{\eval(\@currentlabel)}{\eval(\thepage)}}

```

```

31 \newcommand\slabel[1]{%
32   \@bsphack
33   \if@filesw
34     \let\thepage\relax
35     \def\protect{\noexpand\noexpand\noexpand}%
36     \edef\@tempa{\write\auxout{\string
37       \newlabel{#1}{{\thesubequation}{\thepage}}}}%
38     \expandafter\@tempa
39     \if@nobreak \ifvmode\nobreak\fi\fi
40   \fi\@esphack}

```

`subeqnarray` The `subeqnarray` environment steps the equation counter, sets the subequation counter equal to 1 and behaves much like the `eqnarray` environment. Note the `\@currentlabel` is defined to use the equation counter. This is done so that an

entire array can be referred to using the value of the equation counter. Hence the need for the `\slabel` command.

```

41 \newenvironment{subeqnarray}%
42   {\stepcounter{equation}%
43    \def\@currentlabel{\p@equation\theequation}%
44    \global\c@subequation\@ne
45    \global\@eqnswtrue\m@th
46    \global\@eqcnt\z@\let\\@\csname cr
47    \subeqn@start
48    \bgroup\hskip\@centering
49    \$\displaystyle\tabskip\z@skip\#\$\@eqnse
50    &\global\@eqcnt\@ne \hskip \tw@arraycolsep \hfil\#\$\hfil
51    &\global\@eqcnt\tw@ \hskip \tw@arraycolsep
52    \$\displaystyle\#\$\hfil \tabskip\@centering
53    &\global\@eqcnt\thr@%
54    \hbox to\z@\bgroup\hss\egroup\tabskip\z@skip\cr}
55  {\@csname cr\egroup \$\$global\@ignoretrue}

```

`\@csname cr` These macros handle the user command `\\";` they are adapted from the ones used or the `eqnarray` environment.

First the presence of a `*` detected and the right penalty selected.

```

56 \def\@subeqncr{{\ifnum0='}\fi\@ifstar{\global\@eqpen\@M
57   \global\@eqpen\interdisplaylinepenalty \y@subeqncr}}

```

`\y@subeqncr` This macro is called by `\@subeqncr` and checks if the user requested any extra vertical space. It calls `\@xsubeqncr` with the wanted amount of space as its argument.

```
58 \def\@subeqncr{\@ifnextchar [{\@xsubeqncr[\z@skip]}}
```

`\@xsubeqncr` This macro calls `\@subeqncr` to put in extra `\&`'s if needed, generating an error if the number of columns is too large. Then the penalty selected earlier and the white space requested are inserted.

```

59 \def\@xsubeqncr[#1]{\ifnum0='}\fi\@subeqncr
60   \noalign{\penalty\@eqpen\vskip\jot\vskip #1\relax}}

```

`\@subeqncr` Check the number of columns, and insert extra `\&` if needed. If there appear to be more than 3 columns an error is signalled.

```

61 \def\@subeqncr{\let\@tempa\relax
62   \ifcase\@eqcnt \def\@tempa{\& \& \&}\or \def\@tempa{\& \& \& \&}\else
63   \let\@tempa\empty
64   \@latexerr{Too many columns in subeqnarray environment}\@ehc\fi
65   \global\@eqnsw\@subeqnnum\refstepcounter{subequation}\fi
66   \global\@eqnswtrue\global\@eqcnt\z@\cr}
67 
```

`subeqnarray*` This environment is basically the same as the `eqnarray` environment, but it is provided just or completeness.

```

68 \newenvironment{subeqnarray*}%
69   {\def\@subeqncr{\nonumber\@subeqncr}\subeqnarray}
70   {\global\advance\c@equation\m@ne\nonumber\endsubeqnarray}

```

\@ssubeqnrcr This is used in the `esubeqnarray*` environment.

```
71 \let\@ssubeqnrcr\@subeqnrcr
72 </package>
73 <*sample>
```

5 An example of the use of this package

When you run the following document through L^AT_EX you will see the difference between the `subeqnarray` and `eqnarray` environments.

```
74 <*sample>
75 \documentclass[fleqn]{article}
76 \usepackage{subeqnarray}
77 \begin{document}
78 This document shows an example of the use of the \emph{subeqnarray}
79 environment. Here is one:
80 \begin{subeqnarray}
81 \label{eqw}
82 \label{eq0}
83 x &= & a \times b \\
84 \label{eq1}
85 &= & z + t \\
86 \label{eq2}
87 &= & z + t
88 \end{subeqnarray}
89 The first equation is number^\ref{eq0}, the last is^\ref{eq2}. The
90 equation as a whole can be referred to as equation^\ref{eqw}.
91
92 To show that equation numbers behave normally, here's an
93 \emph{eqnarray} environment.
94 \begin{eqnarray}
95 \label{eq10}
96 x &= & a \times b \\
97 \label{eq11}
98 &= & z + t \\
99 \label{eq12}
100 &= & z + t
101 \end{eqnarray}
102
103 These are equations^\ref{eq10},^\ref{eq11} and^\ref{eq12}.
104 \end{document}
105 </sample>
```

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	D	J
\@@subeqnacr 55, 59, <u>61</u>	\DeclareOption	\jot 60
\@M 56 10, 13, 15, 24, 28	
\@auxout 36	\def 3, 11, 14, 16,	L
\@bsphack 32	25, 35, 43, 56,	\label 81, 95, 97, 99
\@centering 26, 48, 52	58, 59, 61–63, 69	\let 34, 46, 61, 64, 71
\@currentlabel 43	\displaystyle 49, 52	\linewidth 23
\@ehc 65	\displaywidt 12, 27	\Lopt 5
\@empty 64	\documentclass 75	
\@eqcnt 46,		M
50, 51, 53, 62, 67		\m@ne 70
\@eqnse 49	\edef 36	\m@th 45
\@eqnswtrue 45, 67	\egroup 54, 55	\mathindent 17
\@eqpen 56, 57, 60	\else 63	
\@esphack 40	\emph 78, 93	N
\@ifnextchar 58	\end 88, 101, 104	\newcommand 31
\@ifstar 56	\endsubeqnarray 70	\newcounter 2
\@ignoretrue 55	environments:	\newenvironment 41, 68
\@lateerr 65	subeqnarray 41	\newlabel 37
\@ne 44, 50	subeqnarray* 68	\noalign 60
\@ssubeqnacr 69, <u>71</u>	\everycr 23, 27	\nobreak 39
\@subeqnacr 46, <u>56</u> , 69, 71	\ExecuteOptions 29	\noexpand 35
\@subeqnnum 7, 11, 14, 66	\expandafter 38	\nonumber 69, 70
\@tempa 36, 38, 61–64, 66		
\@xsubeqnacr 58, <u>59</u>		O
\@ysubeqnacr 57, 58, <u>58</u>	\fi 19, 39,	\OptionNotUsed 28
\` 46, 83, 85, 96, 98	40, 56, 59, 65, 66	\or 62, 63
A	G	P
\abovedisplayskip 22	\global 44–46, 50, 51, 53, 55–57, 67, 70	\p@ 11
\abovedisplayshortskip 18–22		\p@equation 43
\advance 19, 70	\halign 23, 27	\partopsep 19
\alph 3	\hbox 11, 54	\penalty 60
\arraycolsep 50, 51	\hfil 50, 52	\ProcessOptions 30
	\hskip 12, 48, 50, 51	\protect 35
B	\hss 54	
\begin 9, 77, 80, 94		R
\belowdisplayshortskip 21		\ref 89, 90, 103
\belowdisplayskip 20	\if@eqnsw 66	\refstepcounter 66
\bgroup 48, 54	\if@filesw 33	\relax 34, 60, 61
	\if@nobreak 39	\reset@font 11, 14
C	\ifcase 62	\rlap 11
\c@equation 70	\ifnum 56, 59	\rmfamily 11, 14
\c@subequation 1, 44	\ifvmode 19, 39	
\cr 54, 67	\interdisplaylinepenalty 57	S
		\label 31, 82, 84, 86
		\stepcounter 42
		\string 36
		\subeqn@start 16, 25, 47

\subeqnarray	69	\thepage	34, 37	V	
subeqnarray (environment)	41	\thesubequation	3, 12, 14, 37	\vskip	60
subeqnarray* (environment)	68	\thr@@	53	W	
		\times	83, 96	\write	36
		\topsep	18		
		\tw@	50, 51	Z	
T					
\tabskip	17, 26, 49, 52, 54	U		\z@	46, 54, 67
\theequation	3, 43	\usepackage	76	\z@skip	49, 54, 58

Change History

1.1					
	General: Fixed bug in subeqnarray* environment				1
2.0					
	General: Added support for the fleqn option				1
	Added support for the leqno option				1
2.1					
	General: Upgrade for LaTeX2e				1
v2.1b					
	General: Changed licensing remarks to use LPPL				1